

Sewing Pattern — Blouse 8004

Recommendations on fabric: knit fabric.

Seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance 1 cm on all edges, on hem and sleeve hem – 2 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 1 detail.
2. Lower front part – 1 detail.
3. Upper front part – 2 details.
4. Sleeve – 2 details.

Advice: use special elastic seam or zigzag seam to stitch the parts together. When oversteaching, cut the seam allowances to 0.6 — 0.8 cm. The seam allowance on the edge of the garment is stitched with double seam to ensure stretchiness.

INSTRUCTIONS:

1. Serge neckline on upper front part. Fold to wrong side, press and topstitch. Make plaits according to notches.
2. Put right upper front onto left upper front and pin together. Sew bottom front part to upper front parts, serge and press.
3. Sew shoulder seams. Attention: back shoulder edge is 1 cm longer than front shoulder edge (seam allowance for back neckline). Press towards back piece.
4. Sew side seams. Serge and press.
5. Sew sleeve seams. Serge and press.
6. Sew shoulders into armholes, matching notches. Serge and press.
7. Serge hem, sleeve hem and back neckline. Fold to wrong side, press and topstitch.

TECHNICAL DRAWING:

